

D05 Stack Valves

Flow Control Valves: D05

Hand Knob Adjustment
Sandwich Thickness 55 mm



Valves:

DGMFN 5 Y A2W-41
DGFN 5 X A2W-41
DGMFN 5 Y B2W-41
DGMFN 5 X B2W-41
DGMFN 5 Y A2W B2W-41
DGMFN 5 X A2W B2W-41

Description:

Flow Control Meter-out A port
Flow Control Meter-in A Port
Flow Control Meter-out B port
Flow Control Meter-in B port
Flow Control Meter-out A & B ports
Flow Control Meter-in A & B ports

Check Valves: D05

Sandwich Thickness 55 mm

Valves:

DGMDC 5 X TL-41
DGMDC 5 X AL-41
DGMDC 5 X BL-41
DGMDC 5 Y PL-41
DGMDC 5 X TR-41
DGMDC 5 X AR-41
DGMDC 5 X BR-41
DGMDC 5 Y PR-41

Description:

Free flow away from actuator, Check in T port, 5 psi
Free flow away from actuator, Check in A port, 5 psi
Free flow away from actuator, Check in B port, 5 psi
Free flow towards actuator, Check in P port, 5 psi
Free flow away from actuator, Check in T port, 60 psi
Free flow away from actuator, Check in A port, 60 psi
Free flow away from actuator, Check in B port, 60 psi
Free flow towards actuator, Check in P port, 60 psi

*Note: See page 7 for spool function chart.
D05 valves have (4) # 10-24"x (45mm) 1 3/4" bolts included.*