

D03 Stack Valves

PO Check Valves: D03

14.5 psi check cracking pressure
Sandwich Thickness 40 mm



Valves:

DGMPC-3ABK BAK-41

DGMPC-3ABK-41

DGMPC-3BAK-41

Description:

Dual Cross over checks

Check in "A", pilot from "B"

Check in "B", pilot from "A"

Reducing Valves: D03

Pressure reduced in "P", piloted from "P"
Hand knob Adjustment
Sandwich Thickness 40 mm

Valves:

DGMX2 3 PP B-41

DGMX2 3 PP C-41

DGMX2 3 PP F-41

DGMX2 3 PA B-41

DGMX2 3 PA C-41

DGMX2 3 PA F-41

DGMX2 3 PB B-41

DGMX2 3 PB C-41

DGMX2 3 PB F-41

Description:

Adjustment range 50 to 1000 psi, Reduced in P

Adjustment range 145 to 2000 psi, Reduced in P

Adjustment range 290 to 3625 psi, Reduced in P

Adjustment range 50 to 1000 psi, Reduced in A

Adjustment range 145 to 2000 psi, Reduced in A

Adjustment range 290 to 3625 psi, Reduced in A

Adjustment range 50 to 1000 psi, Reduced in B

Adjustment range 290 to 3625 psi, Reduced in B

Adjustment range 290 to 3625 psi, Reduced in B

*Note: See page 7 for spool function chart.
D03 valves have (4) # 10-24"x (45mm) 1 3/4" bolts included.*