

DG4V3(S) – Hydraulic Directional Valve D03

Subplate / Manifold Mounted
Solenoid Operated
P, A, B Pressure Rated 5000 psi (350 bar)
T Pressure Rate at 1450 psi (100 bar)
Flows to 14 GPM (54 l/m)
Wiring box is 1/2" NPT thread
DIN female connection plugs included



120 VAC Coils 60 HZ – D03 (B) Coil

Spool	Valves	Description
2C	DG4V3S2CMFTWLB560	Wiring box, spring centered, two solenoids, light kit, 120 VAC 50/60 HZ
2C	DG4V3S2CMUB560	Din connectors, spring centered, two solenoids, 120 VAC, 50/60 HZ
6C	DG4V3S6CMFTWLB560	Wiring box, spring centered, two solenoids, light kit, 120 VAC, 50/60 HZ
6C	DG4V3S6CMUB560	Din connectors, spring centered, two solenoids, 120 VAC, 50/60 HZ
8C	DG4V3S8CMFTWLB560	Wiring box, spring centered, two solenoids, light kit, 120 VAC, 50/60 HZ
8C	DG4V3S8CMUB560	Din connectors, spring centered, two solenoids 120 VAC, 50/60 HZ
2A	DG4V3S2AMFTWLB560	Spring Offset, "A" port, Wiring Box, single Solenoid light kit, 120 VAC 50/60 HZ
2A	DG4V3S2AMUB560	Spring Offset, "A" port, Din Connector, single, solenoid, 120 VAC 50/60 HZ
0C	DG4V3S0CMFTWLB560	Wiring box, spring centered, two solenoids, light kit, 120 VAC, 50/60 HZ
7C	DG4V3S7CMFTWLB560	Wiring box, spring centered, two solenoids, light kit, 120 VAC, 50/60 HZ

*Note: See page 7 for spool function chart.
D03 valves have (4) # 10-24"x (45mm) 1 3/4" bolts included.*



DG4V3(S) – Hydraulic Directional Valve D03

12 VDC Coils – D03 (G) Coil

Spool	Valves	Description
2C	DG4V3S2CMFTWLG560	Wiring box, spring centered, two solenoids, 12 VDC
2C	DG4V3S2CMUG560	Din connectors, spring centered, two solenoids 12 VDC
6C	DG4V3S6CMFTWLG560	Wiring box, spring centered, two solenoids, 12 VDC
6C	DG4V3S6CMUG560	Din connectors, spring centered, two solenoids 12 VDC
2A	DG4V3S2AMFTWLG560	Spring Offset, "A" port, Wiring Box, single solenoid, 12 VDC
2A	DG4V3S2AMU560	Spring Offset, "A" port, Din Connector, single solenoid, 12 VDC

24 VDC Coils – D03 (H) Coil

Spool	Valves	Description
2C	DG4V3S2CMFTWLH560	Wiring box, spring centered, two solenoids, light kit, 24 VDC
2C	DG4V3S2CMUH560	Din connectors, spring centered, two solenoids 24 VDC
6C	DG4V3S6CMFTWLH560	Wiring box, spring centered, two solenoids, light Kit, 24 VDC
6C	DG4V3S6CMUH560	Din connectors, spring centered, two solenoids 24 VDC
2A	DG4V3S2AMFTWLH560	Spring Offset, "A" port, Wiring Box, single solenoid, light kit, 24 VDC
2A	DG4V3S2AMUH560	Spring Offset, "A" port, Din Connector, single Solenoid, 24 VDC
7C	DG4V3S7CMFTWLH560	Din connectors, spring centered, two solenoids, 24 VDC

*Note: See page 7 for spool function chart.
D03 valves have (4) # 10-24"x (45mm) 1 3/4" bolts included.*