

DG4S4 – Hydraulic Directional D05

Subplate / Manifold Mounted
Solenoid Operated
P, A, B Pressure Rated 4500 psi (310 bar)
T Pressure Rate at 1000 psi (69 bar)
Flows to 21.5 GPM (80 l/m)
Wiring box is 1/2" NPT thread
DIN female connection plugs included



120 VAC Coils 60 HZ – D05 (B) Coil

Spool	Valves	Description
2A	DG4S4LW012AB60	Wiring box, spring offset to "A" Single solenoid, Light kit, 120 VAC, 50/60 HZ
2A	DG4S4012AUB60	Din connectors, spring offset to "A" Single solenoid, 120 VAC, 50/60 HZ
2C	DG4S4LW012CB60	Wiring box, spring centered, two solenoids, Light kit, 120 VAC, 50/60 HZ
2C	DG4S4012CUB60	Din connectors, spring centered, two solenoids, 120 VAC, 50/60 HZ
6C	DG4S4LW016CB60	Wiring box, spring centered, two solenoids, Light kit, 120 VAC, 50/60 HZ
6C	DG4S4016CUB60	Din connectors, spring centered, two solenoids, 120 VAC, 50/60 HZ
8C	DG4S4LW018CB60	Wiring box, spring centered, two solenoids, Light kit, 120 VAC, 50/60 HZ
8C	DG4S4018CUB60	Din connectors, spring centered, two solenoids, 120 VAC, 50/60 HZ
7C	DG4S4LW017CB60	Wiring box, spring centered, two solenoids, Light kit, 120 VAC, 50/60 HZ

*Note: See page 7 for spool function chart.
D05 valves have (4) # 10-24"x (45mm) 1 3/4" bolts included.
Kit Part Number WFBK702504*



DG4S4 – Hydraulic Directional D05

12 VDC Coils – D05 (G) Coil

Spool	Valves	Description
2C	DG4S4LW012CG60	Wiring box, spring centered, two solenoids, Light kit, 12 VDC
2A	DG4S4LW012AG60	Wiring box, spring offset to “A” Single solenoid, Light kit, 12 VDC
2C	DG4S4012CUG60	Din connectors, spring centered, two solenoids, 12 VDC
2A	DG4S4012AUG60	Din connectors, spring offset to “A” Single solenoid, Light kit, 12 VDC
6C	DG4S4LW016CG60	Wiring box, spring centered, two solenoids, Light kit, 12 VDC
6C	DG4S4016CUG60	Din connectors, spring centered, two solenoids, 12 VDC
7C	DG4S4017CUG60	Din connectors, spring centered, two solenoids, 12 VDC

24 VDC Coils – D05 (H) Coil

Spool	Valves	Description
2C	DG4S4LW012CH60	Wiring box, spring centered, two solenoids, Light kit, 24 VDC
2A	DG4S4LW012AH60	Wiring box, spring offset to “A” Single solenoid, Light kit, 24 VDC
2C	DG4S4012CUH60	Din connectors, spring centered, two solenoids, 24 VDC
2A	DG4S4012AUH60	Din connectors, spring offset to “A” Single solenoid, Light kit, 24 VDC
6C	DG4S4LW016CH60	Wiring box, spring centered, two solenoids, Light kit, 24 VDC
6C	DG4S4016CUH60	Din connectors, spring centered, two solenoids, 24 VDC
7C	DG4S4017CUH60	Din connectors, spring centered, two solenoids, 24 VDC

*Note: See page 7 for spool function chart.
D05 valves have (4) # 10-24”x (45mm) 1 3/4” bolts included.
Kit Part Number WFBK702504*